



RPM	MODELLO MODEL	PORTATA FLOW		PRESSIONE PRESSURE		POTENZA POWER		PESO WEIGHT
		l/min	GPM	bar	PSI	HP	kW	Kg
1450	PSC 11/15 S	11.0	2.9	150	2200	4.2	3.1	6.6
	PSC 13/15 S	13.0	3.4	150	2200	5.0	3.7	6.6
	MSC 16/20 S	16.0	4.2	200	3000	8.2	6.0	10.4
	MSC 20/20 S	20.0	5.3	200	3000	10.3	7.5	10.4
	GSC 27/20 S	27.0	7.1	200	3000	13.8	10.2	19.4
	GSC 34/20 S	34.0	9.0	200	3000	17.4	12.8	19.4
	GSC 42/15 S	42.0	11.1	150	2200	16.1	11.9	19.4
	GSC 50/15 S •	50.0	13.2	150	2200	19.2	14.1	19.4

S = Albero Maschio 24 mm  
S = Male Shaft 24 mm

Materiale Testata: Acciaio Inox AISI 316 L  
Head material: SS AISI 316L

• Minimo 0.1 bar (1.5 PSI) di pressione in entrata / Min. 0.1 bar (1.5 PSI) inlet pressure

### Dimensioni d'ingombro (mm) - Overall Dimensions (mm)

